




# Bearing Unit

## ZGKU 309 2S

### Bearing Unit

Packer roller, subsoiler, stubble cultivator



### Technical Specification

|      |                            |               |
|------|----------------------------|---------------|
| d    | Bore diameter              | 45 mm         |
| d1   | Centering diameter         | 74 mm         |
| L1   | Housing overall width      | 152 mm        |
| J1   | Distance between the holes | 120 mm        |
| L2   | Housing overall width      | 150 mm        |
| J2   | Distance between the holes | 120 mm        |
| A    | Overall width              | 66.9 mm       |
| A1   | Flange width               | 18 mm         |
| A2   | Flange width               | 12 mm         |
| A3   | Centering diameter height  | 7 mm          |
| T    | Threaded hole size         | 4xM12x1.25 mm |
| H    | Hole diameter              | 4x12.3 mm     |
| kg   | Mass                       | 5.6 kg        |
| Cdyn | Dynamic load rating        | 52.7 kN       |
| Co   | Static load rating         | 31.5 kN       |
| Pu   | Fatigue load limit         | 1.32 kN       |

## Sealing

### S SEAL / S SEAL (2S)

Single lip seal with the labyrinth between the sheet part and the rubber lip which conducts the contact sealing. The friction and speeds are the same as with RS but provides much better protection against the rough impurity particles. This is very good sealing system: the sheet part protects the seal from the soil, dust and rough particles. At the same time makes the labyrinth with the rubber part. The rubber part provides contact sealing which prevents penetration of finer impurities, water, moisture, steam etc. Suitable for neutral conditions because of the presence of the foreign materials. It is used with the Y bearing (standard) and deep groove ball bearings.

